

BATTERY CONNECTORS

CTC-3002 1~2 PINS
SINGLE TYPE H=2.2mm
Pitch=3.00mm

- Rating: AC/DC125V 1.5A
- Force: 80±20gf
- Package: 1,500 Pcs/Reel

1 PIN

2 PINS

Pad Layout

CTC-3003 3~4 PINS
SINGLE TYPE H=3.0mm
Pitch=3.20mm

- Rating: AC/DC125V 1.5A
- Force: 90±15gf
- Package: 1,000 Pcs/Reel

3 PINS

4 PINS

Pad Layout

| PINS | A | B | C |
|------|------|-----|-----|
| 3 | 9.0 | 6.4 | 6.4 |
| 4 | 12.2 | 9.6 | 9.6 |

CTC-3008 6 PINS
Pitch=3.00mm

- Rating: AC/DC125V 2.0A
- Force: 100±30gf
- Package: 500 Pcs/Reel

Pad Layout

CTC-3027 3 PINS
Pitch=2.50mm

- Rating: DC 7V 2.5A
- Force: 70gf Min.
- Life: 10,000 Cycles
- Package: 1,500 Pcs/Reel

Pad Layout

CTC-3028 4 PINS
Pitch=2.50mm

- Rating: DC15V 1A
- Force: 100gf Min.
- Life: 5,000 Cycles

Pad Layout

CTC-3029 5 PINS
Pitch=2.50mm

- Rating: DC 7V 2.5A
- Force: 70gf Min.
- Life: 10,000 Cycles

Pad Layout

CTC-3030 6 PINS

- Rating: DC 15V 3A
- Force: 150gf Min.
- Life: 5,000 Cycles

Pad Layout

BATTERY HOLDER FOR BATTERY: CR2032
NTC-2032-A (SMD TYPE)

- Rating: 3V 220mAh
- Contact Force: 294gf
- Package: 600 Pcs/Reel

Pad Layout