

POTENTIOMETERS

<h3>SVR02K (2ϕ)</h3> <ul style="list-style-type: none"> Power Rating: 0.15W Rotation Angle: Endless Effective 260\pm20° Total Resistance: 220~2.2M$\Omega$$\pm$30% Resistance Taper: B Linear Package: 3,000 Pcs/Reel <p>Circuit CW</p> <p>Pad Layout</p>	<h3>SVR031 (3ϕ)</h3> <ul style="list-style-type: none"> Power Rating: 0.1W Rotation Angle: Endless Effective 250\pm20° Total Resistance: 100~2.2M$\Omega$$\pm$25% Resistance Taper: B Linear Package: 2,000 Pcs/Reel <p>Circuit CW</p> <p>Pad Layout</p>																				
<h3>SVR03KJ (3ϕ)</h3> <ul style="list-style-type: none"> Power Rating: 0.1W Rotation Angle: Endless Effective 250\pm20° Total Resistance: 100~2.2M$\Omega$$\pm$25% Resistance Taper: B Linear Package: 2,000 Pcs/Reel <p>Circuit CW</p> <p>Pad Layout</p>	<h3>SVR05V (5ϕ)</h3> <ul style="list-style-type: none"> Power Rating: 0.2W Rotation Angle: 200\pm20° Total Resistance: 100~1M$\Omega$$\pm$25% Resistance Taper: B Linear <p>Circuit CW</p> <p>Mounting Hole Layout</p>																				
<h3>RK09PH</h3> <ul style="list-style-type: none"> Power Rating: 0.05W Total Resistance: 5KΩ~500K$\Omega$$\pm$20% Total Rotation Angle: 280\pm5° Resistance Taper: B Linear Rotation Torque: 10~80gf \cdot cm Life: 5,000 Cycles <p>Shaft Dimension</p> <table border="1"> <thead> <tr> <th>Shaft L(mm)</th> <th>ϕ</th> </tr> </thead> <tbody> <tr><td>15</td><td>6</td></tr> <tr><td>20</td><td>7</td></tr> <tr><td>25</td><td>7</td></tr> <tr><td>30</td><td>7</td></tr> </tbody> </table> <p>Mounting Hole Layout</p>	Shaft L(mm)	ϕ	15	6	20	7	25	7	30	7	<h3>RK09PV</h3> <ul style="list-style-type: none"> Power Rating: 0.05W Total Resistance: 5KΩ~500K$\Omega$$\pm$20% Total Rotation Angle: 280\pm5° Resistance Taper: B Linear Rotation Torque: 10~80gf \cdot cm Life: 5,000 Cycles <p>Shaft Dimension</p> <table border="1"> <thead> <tr> <th>Shaft L(mm)</th> <th>ϕ</th> </tr> </thead> <tbody> <tr><td>15</td><td>6</td></tr> <tr><td>20</td><td>7</td></tr> <tr><td>25</td><td>12</td></tr> <tr><td>30</td><td>12</td></tr> </tbody> </table> <p>Mounting Hole Layout</p>	Shaft L(mm)	ϕ	15	6	20	7	25	12	30	12
Shaft L(mm)	ϕ																				
15	6																				
20	7																				
25	7																				
30	7																				
Shaft L(mm)	ϕ																				
15	6																				
20	7																				
25	12																				
30	12																				
<h3>RP07PH</h3> <ul style="list-style-type: none"> Power Rating: 0.01W Max. Rating Voltage: DC5V Total Resistance: 5K$\Omega$$\pm$30% Total Rotation Angle: Endless Resistance Taper: B Linear Rotation Torque: 50gf \cdot cm Max. Life: 500,000 Cycles Package: 1,000 Pcs/Reel <p>Electrical Effective Angle 295°</p> <p>Pad Layout</p>	<h3>RP07PV</h3> <ul style="list-style-type: none"> Power Rating: 0.01W Max. Rating Voltage: DC6V Total Resistance: 5K$\Omega$$\pm$30% Total Rotation Angle: Endless Resistance Taper: B Linear Rotation Torque: 50gf \cdot cm Max. Life: 100,000 Cycles <p>Electrical Effective Angle 295°</p> <p>Mounting Hole Layout</p>																				