

PUSH SWITCHES

<p>PTS-041</p> <ul style="list-style-type: none"> Rating: DC3V 50μA~DC14V 200mA Stroke: Full 2.3mm Lock 1.5mm Force: 300±100gf Life: 30,000 Cycles Package: 300 Pcs/Reel <p>PUSH TO LOCK: PTS-041S PUSH NO LOCK: PTS-041N</p>	<p>PTS-043</p> <ul style="list-style-type: none"> Rating: DC3V 50μA~DC14V 200mA Stroke: Full 2.3mm Lock 1.5mm Force: 300±100gf Life: 30,000 Cycles <p>PUSH TO LOCK: PTS-043S PUSH NO LOCK: PTS-043N</p>
<p>PTS-065</p> <ul style="list-style-type: none"> Rating: DC14V 200mA Stroke: Full 2.5 Lock 1.5mm Force: PTS-065 □-C: 300±100gf PTS-065 □-E: 500±150gf Life: 50,000 Cycles Package: 300 Pcs/Reel Operating Temp. Range: -40~+85°C <p>PUSH TO LOCK: PTS-065S PUSH NO LOCK: PTS-065N</p>	<p>PTS-066</p> <ul style="list-style-type: none"> Rating: DC14V 200mA Stroke: Full 2.5 Lock 1.5mm Force: PTS-066 □-C: 300±100gf PTS-066 □-E: 500±150gf Life: 50,000 Cycles Operating Temp. Range: -40~+85°C <p>PUSH TO LOCK: PTS-066S PUSH NO LOCK: PTS-066N</p>
<p>PTS-130 SPDT</p> <ul style="list-style-type: none"> Rating: DC30V 300mA Stroke: Full 3.5 Lock 2.5mm Force: 230±100gf Life: 10,000 Cycles <p>PUSH TO LOCK: PTS-130S PUSH NO LOCK: PTS-130N</p>	<p>PTS-131 DPDT</p> <ul style="list-style-type: none"> Rating: DC30V 300mA Stroke: Full 3.5 Lock 2.5mm Force: 350±100gf Life: 10,000 Cycles <p>PUSH TO LOCK: PTS-131S PUSH NO LOCK: PTS-131N</p>
<p>PUSH NO LOCK PTS-132N DPDT</p> <ul style="list-style-type: none"> Rating: DC30V 300mA Stroke: 2.5mm Force: 200±100gf Life: 10,000 Cycles 	<p>PTS-245 DPDT</p> <ul style="list-style-type: none"> Rating: DC30V 100mA DC 25V 1A Stroke: Full 3.5 Lock 2.5mm Force: 200±100gf Life: 10,000 Cycles(DC 30V) 5,000 Cycles(DC 25V) <p>PUSH TO LOCK : PTS-245S PUSH NO LOCK : PTS-245N</p>