

SENSOR SWITCHES

<p>CLS-085 WITHOUT TAB CLS-085A WITH TAB</p> <ul style="list-style-type: none"> • Rating: DC5V 1mA • Force: 35gf Max. • Life: 100,000 Cycles • Package: 2,500 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>	<p>CLS-086</p> <ul style="list-style-type: none"> • Rating: DC5V 0.1~5mA • Force: 32.3gf Max. • Life: 50,000 Cycles • Package: 1,700 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>								
<p>CLS-087</p> <ul style="list-style-type: none"> • Rating: DC5V 0.5~10mA • Force: 40gf Max. • Life: 100,000 Cycles • Package: 1,000 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>	<p>CLS-088</p> <ul style="list-style-type: none"> • Rating: DC16V 20mA • Force: 69gf Max. • Life: 20,000 Cycles <p>Circuit</p>								
<p>CLS-089</p> <ul style="list-style-type: none"> • Rating: DC12V 100mA • Force: 69gf Max. • Life: 50,000 Cycles <p>Circuit</p> <p>Mounting Hole Layout</p>	<p>CLS-090</p> <ul style="list-style-type: none"> • Rating: DC12V 100mA • Force: 69gf Max. • Life: 50,000 Cycles <p>Circuit</p> <p>Mounting Hole Layout</p>								
<p>CLS-091</p> <ul style="list-style-type: none"> • Rating: DC5V 10mA • Force: 69gf Max. • Life: 50,000 Cycles <p>Circuit</p> <p>Mounting Hole Layout</p>	<p>CLS-092</p> <ul style="list-style-type: none"> • Rating: DC5V 20mA • Force: 100gf Max. • Life: 20,000 Cycles <p>Circuit</p> <p>Switching Timing: Shorting Timing Chart</p> <table border="1"> <tr> <td>1-2</td> <td>ON</td> <td>OFF</td> <td>ON</td> </tr> <tr> <td>2-3</td> <td>OFF</td> <td>ON</td> <td>OFF</td> </tr> </table> <p>Mounting Hole Layout</p>	1-2	ON	OFF	ON	2-3	OFF	ON	OFF
1-2	ON	OFF	ON						
2-3	OFF	ON	OFF						