

SLIDE SWITCHES

8SS1011 1P2T

- Rating: AC125V 6A
- Stroke: 2.2mm
- Force: 250±150gf
- Life: 30,000 Cycles

Circuit

Panel Cut-Out Dim.

Stroke 2.2

SSS-1205 1P2T

- Rating: DC30V 300mA
- Stroke: 3.5mm
- Force: 200±100gf
- Life: 10,000 Cycles

Circuit

Panel Cut-Out Dim.

SSS-2217 2P2T

- Rating: DC30V 300mA
- Stroke: 2.0mm
- Force: 250±100gf
- Life: 5,000 Cycles

Circuit

Mounting Hole Layout

Stroke 2

SSS-2218 2P2T

- Rating: AC125V 1A
- Stroke: 3.5mm
- Force: 300±200gf
- Life: 5,000 Cycles

Circuit

Panel Cut-Out Dim.

SSS-2219 2P2T

- Rating: AC125V 1A
DC30V 1A
- Stroke: 3.0mm
- Force: 300±150gf
- Life: 5,000 Cycles

Circuit

Mounting Hole Layout

Stroke 3

SST-2219 2P2T

- Rating: AC125V 1A
DC30V 1A
- Stroke: 3.0mm
- Force: 300±150gf
- Life: 10,000 Cycles

Circuit

Mounting Hole Layout

SSS-2220 2P2T

- Rating: AC125V 1A
DC30V 1A
- Stroke: 3.0mm
- Force: 300±150gf
- Life: 5,000 Cycles

Circuit

Mounting Hole Layout

Stroke 3

SST-2301 2P3T

- Rating: DC30V 200mA
- Stroke: 2.0mm
- Force: Side → Center: 250±100gf
Center → Side: 300±100gf
- Life: 10,000 Cycles

Circuit

Mounting Hole Layout

Stroke 2