

# SLIDE SWITCHES

**SSS-1224** L=2.0mm 1P2T  
**SSS-1225** L=4.0mm

- Rating: DC12V 100mA
- Stroke: 2.0mm
- Force: 350±150gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SST-1234** L=2.0mm 1P2T  
**SST-1235** L=4.0mm  
**SST-1236** L=5.6mm

- Rating: DC12V 100mA
- Stroke: 2.0mm
- Force: 250±150gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SSS-1226** L=6.0mm 1P2T  
**SSS-1227** L=9.0mm  
**SSS-1228** L=12.0mm

- Rating: DC30V 100mA
- Stroke: 2.0mm
- Force: 250±120gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SST-1237** L=6.0mm 1P2T  
**SST-1238** L=9.0mm  
**SST-1239** L=12.0mm

- Rating: DC30V 100mA
- Stroke: 2.0mm
- Force: 250±120gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SSS-1308** L=6.0mm 1P3T  
**SSS-1309** L=9.0mm  
**SSS-1310** L=12.0mm

- Rating: DC30V 100mA
- Stroke: 2.0mm
- Force: Side → Center: 220±100gf  
Center → Side: 300±150gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SST-1310** L=6.0mm 1P3T  
**SST-1311** L=9.0mm

- Rating: DC30V 100mA
- Stroke: 2.0mm
- Force: Side → Center: 220±100gf  
Center → Side: 300±150gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SSS-1401** L=6.0mm 1P4T  
**SSS-1402** L=9.0mm  
**SSS-1403** L=12.0mm

- Rating: DC30V 100mA
- Stroke: 2.0mm
- Force: ① → ②, ③ → ④ : 300±150gf  
① → ③, ③ → ① : 250±120gf  
② → ①, ④ → ③ : 200±100gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**

**SST-1401** L=6.0mm 1P4T  
**SST-1402** L=9.0mm

- Rating: DC30V 100mA
- Stroke: 2.0mm
- Force: ① → ②, ③ → ④ : 300±150gf  
① → ③, ③ → ① : 250±120gf  
② → ①, ④ → ③ : 200±100gf
- Life: 10,000 Cycles

**Circuit**  
**Mounting Hole Layout**