

SMD TACTILE SWITCHES

<p>STS-036 H=2.5mm</p> <ul style="list-style-type: none"> • Rating: DC12V 20mA • Stroke: 0.15mm • Force: STS-036-A:180±50gf STS-036-B:240±60gf • Life: STS-036-A:100,000 Cycles STS-036-B:50,000 Cycles • Package: 3,000 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>	<p>STS-086 H=2.5mm</p> <ul style="list-style-type: none"> • Rating: DC12V 20mA • Stroke: 0.2mm • Force: 180±50gf • Life: 50,000 Cycles • Package: 3,000 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>
<p>GROUND TERMINAL TYPE STS-084 H=4.3mm</p> <ul style="list-style-type: none"> • Rating: DC12V 50mA • Stroke: 0.25mm • Force: 160±50gf • Life: 100,000 Cycles • Package: 1,200 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>	<p>DUST PROOF STS-126-A H=3.1mm STS-126-B</p> <ul style="list-style-type: none"> • Rating: DC12V 50mA • Stroke: 0.25mm • Force: STS-126-A: 180±50gf STS-126-B: 280±50gf • Life: STS-126-A: 300,000 Cycles STS-126-B: 200,000 Cycles • Package: 1,500 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>
<p>STS-200 H=1.8mm</p> <ul style="list-style-type: none"> • Rating: DC12V 50mA • Stroke: 0.12mm • Force: 140±50gf • Life: 100,000 Cycles • Package: 3,000 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>	<p>WATER & DUST PROOF : IP67 STS-218 H=7.2mm</p> <ul style="list-style-type: none"> • Rating: DC12V 50mA • Stroke: 0.4mm • Force: 250±80gf • Life: 300,000 Cycles • Package: 800 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>
<p>STS-219 H=1.5mm</p> <ul style="list-style-type: none"> • Rating: DC12V 50mA • Stroke: 0.15mm • Force: 160±50gf • Life: 200,000 Cycles • Package: 3,000 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>	<p>WATER & DUST PROOF : IP67 STS-222-A1 H=4.3mm STS-222-B1 H=5.0mm</p> <ul style="list-style-type: none"> • Rating: DC12V 50mA • Stroke: 0.2mm • Force: 160±50gf • Life: 200,000 Cycles • Package: 1,200 Pcs/Reel <p>Circuit</p> <p>Pad Layout</p>