

# ROCKER SWITCHES

**SPST**  
**R13-66AB ON-OFF**  
**R13-66FB (ON)-OFF**  
 (ON)=Momentary

- Rating: cULus: AC125V 16A / AC250V 10A  
 DEMKO / ENEC: AC125V / 250V 16(4)A  
 CQC: AC125V 10A / AC250V 6A
- Life: 10,000 Cycles

Thickness of Mounting Board	C
0.75-1.25mm	19.2mm
1.25-2mm	19.4mm
2-3mm	19.8mm

Switching Function	Rocker Marking			
POLES	SPST	SPST	SPST	SPST
ON-OFF	R13-66 AB0	R13-66 AB1	R13-66 AB2	R13-66 AB3
(ON)-OFF	R13-66 FB0	R13-66 FB1	R13-66 FB2	R13-66 FB3

(ON):Momentary

**SPDT**  
**R13-66CB ON-ON**

- Rating: cULus: AC125V 16A / AC250V 10A  
 DEMKO / ENEC: AC125V / 250V 16(4)A  
 CQC: AC125V 10A / AC250V 6A
- Life: 10,000 Cycles

Thickness of Mounting Board	C
0.75-1.25mm	19.2mm
1.25-2mm	19.4mm
2-3mm	19.8mm

Switching Function	Rocker Marking	
POLES	SPDT	SPDT
ON-ON	R13-66CB0	R13-66CB5

**SPST**  
**R13-66AB4-R/A ON-OFF**

- Rating: cULus: AC125V 16A / AC250V 10A  
 DEMKO / ENEC: AC125V / 250V 16(4)A  
 CQC: AC125V 10A / AC250V 6A
- Life: 10,000 Cycles

Mounting Hole Layout

Panel Mounting Hole

Thickness of Mounting Board	C
0.75-1.25mm	19.2mm
1.25-2mm	19.4mm
2-3mm	19.8mm

**SPDT**  
**R13-66CB4-R/A ON-ON**

- Rating: cULus: AC125V 16A / AC250V 10A  
 DEMKO / ENEC: AC125V / 250V 16(4)A  
 CQC: AC125V 10A / AC250V 6A
- Life: 10,000 Cycles

Mounting Hole Layout

Panel Mounting Hole

Thickness of Mounting Board	C
0.75-1.25mm	19.2mm
1.25-2mm	19.4mm
2-3mm	19.8mm

**DPST**  
**R13-73AB ON-OFF**

- Rating: cULus: AC125V 8A / AC250V 4A  
 DEMKO / ENEC: AC 125V/250V 10(2)A  
 CQC: AC125V 10A / AC250V 6A
- Life: 10,000 Cycles

Panel Mounting Hole

Thickness of Mounting Board	C
0.75-1.25mm	19.2mm
1.25-2mm	19.4mm
2-3mm	19.8mm

Switching Function	Rocker Marking		
POLES	DPST	DPST	DPST
ON-OFF	R13-73 AB0	R13-73 AB1	R13-73 AB4

**WITH ILLUMINATION**  
**SPST**  
**R13-90PBRR4 ON-OFF**

- Rating: cULus: AC125V 16A / AC250V 10A
- Life: 10,000 Cycles
- Lamp: Red, AC125V / 250V

Panel Mounting Hole

Thickness of Mounting Board	C
0.75-1.25mm	30.2mm
1.25-2mm	30.4mm
2-3mm	30.8mm

**DPST**  
**R13-87AB ON-OFF**

- Rating: cULus: AC125V 16A / AC250V 10A  
 CQC: AC125V 16A / AC250V 10A
- Life: 10,000 Cycles

Panel Mounting Hole

Thickness of Mounting Board	C
0.75-1.25mm	30.2mm
1.25-2mm	30.4mm
2-3mm	30.8mm

Switching Function	Rocker Marking			
POLES	DPST	DPST	DPST	DPST
ON-OFF	R13-87 AB0	R13-87 AB1	R13-87 AB2	R13-87 AB3

**WITH ILLUMINATION**  
**DPST**  
**R13-87BB ON-OFF**

- Rating: cULus: AC125V 16A / AC250V 10A  
 CQC: AC125V 16A / AC250V 10A
- Life: 10,000 Cycles

Panel Mounting Hole

Thickness of Mounting Board	C
0.75-1.25mm	30.2mm
1.25-2mm	30.4mm
2-3mm	30.8mm

Switching Function	Rocker Marking		
POLES	DPST	DPST	DPST
Lamp	Green	Red	Yellow
ON-OFF	R13-87 BBG0	R13-87 BBR0	R13-87 BBAR0