



P.C.B TERMINAL POSITION

CIRCUIT ARRANGEMENT



SOLDERING CONDITIONS

	Temperature (°C)	Time (Sec.)
Auto Soldering	255 Max.	5 Max.

SPECIFICATIONS

- 1. Rating : DC 12V 50 mA
- 2. Contact Resistance : 500mΩ Max.
- 3. Insulation Resistance : 100MΩ Min. at DC 100V
- 4. Dielectric Strength : AC 110V for 1 Minute
- 5. Operating Force : 260±70gf
- 6. Stroke : 0.25±0.1 mm
- 7. Life : 100,000 Cycles
- 8. Carrier Tape : 900 Pcs
- 9. Operating Temperature Range : -20~+70°C
- 10. Storage Temperature Range : -30~+80°C

REVISION:		DATE:		REVISION:		DATE:	
UNIT:mm		THIRD ANGLE PROJECTION METHOD		TOL. UNLESS OTHERWISE STATED:±0.3		CODE NO.: HCH-1514-1 (A)	
ISSUED		CONFIRMED		HCH HORNG CHIH ISO9001 Certified ISO14001 Certified 鴻琪股份有限公司		PART NO.	
<i>John</i> 2012.06.22		<i>Elvis</i> 2012.06.22				PTS-115	