





5	Contact	Stainless Steel	Ag Clad	
4	Terminal	Brass	Ag Plating	
3	Cover	SPCC	Sn Plating	
2	Stem	PPA		UL94HB, Black
1	Case	PPA		UL94HB, Black
No.	Name	Material	Finish	Remarks

Part No.	Height	Package
STS-214	H=3.8mm	2,000 Pcs/Reel
STS-214-B1	H=5.0mm	1,500 Pcs/Reel
STS-214-D1	H=7.0mm	1,000 Pcs/Reel





SET MAREKR KNOB SIZE
(H:3.8mm ONLY)




P.C.B TERMINAL POSITION

CIRCUIT ARRANGEMENT



SOLDERING CONDITIONS

SPECIFICATIONS



- Rating : DC 12V 50mA
- Contact Resistance : 100mΩ Max.
- Insulation Resistance : 100MΩ Min. at DC 100V
- Dielectric strength : AC 250V for 1 Minute
- Operating Force : 160±50 gf
- Stroke : 0.2±0.1 mm
- Life : 500,000 Cycles
- Operating Temperature Range : -20~+70°C
- Storage Temperature Range : -30~+80°C
- Manual soldering : Tip Temperature 350±5°C
Soldering Time 5 Sec.

REVISION:		DATE:		REVISION:		DATE:	
UNIT:mm		THIRD ANGLE PROJECTION METHOD		TOL. UNLESS OTHERWISE STATED:±0.2		CODE NO.: HCH-2391	
ISSUED		CONFIRMED		HCH ISO9001 Certified ISO14001 Certified HORNG CHIH 鴻琪股份有限公司		PART NO. STS-214	
<i>John</i> 2021.03.10		<i>Elvis</i> 2021.03.10					